

**FOTON**

SPECIFICATION

ETX Tipper 6×4

The image is only a reference

Base informations	Drive style	6*4
	Steering wheel position	RHD
	Platform	ETX
	Vehicle model	BJ3253DLPJB-R
	Resource No.	3253DLPJB-0RZA01
Chassis dimension parameters	Wheelbase (mm)	3650+1350
	long(mm)	8650
	width(mm)	2495
	height(mm)	3400
	inner dimension of bucket (L×W×H)	5600×2300×1500
	Plate thickness of bucket (mm)	Side wall : 6mm; Bottom 8mm
Complete vehicle mass parameter	Chassis kerb weight (kg)	12603
	GVW(design) (kg)	25000
	GCW (kg)	/
Complete vehicle performance parameter	Maximum speed (km/h)	77m/h
	Maximum climbing capacity, % (full load)	30%
Cab	Body type	ETX-2490 - Flat Roof
	Carrying number	3
Engine	Engine Model	WD615.50 With WEVB
	Displacement (L)	9.726
	Max power (kw/ps/rpm)	213/290(2200)
	Max torque (Nm/rpm)	1160/(1300-1600)
	Engine Brand	Weichai
	Emission	Euro II
Clutch	Clutch Type	φ430 pull type diaphragm spring clutch
	Plate diameter	Φ430
Gearbox	Gearbox Model	RTD-11509C
	Gearbox Brand	FAST
Suspension	Front suspension/leaf spring number	9
	Rear suspension/leaf spring number	12
Front axle	Front axle Rated load	7.5T
	Front axle Brake type	Drum brakes
Rear axle	Rear axle Model	STYRE 13T Double reduction
	Rated load/gear ratio	13T/5.73
	Rear axle Brake type	Drum brakes
Tyre	Tyre Model	12R22.5
	Tyre Quantity	10+1
Frame	External width (mm)	865
	Stringer cross section (mm)	(243/320)X90X(8+7)
Steering Gear	Steering Gear Model	ZF8098
Fuel tank	Fuel tank Cubage and material	350